



Permasolid® HS Wet-on-Wet Speed Surfacer 5550.

Wet-on-Wet Speed Surfacer for higher throughput and exceptional appearance.

The Permasolid® HS Wet-on-Wet Speed Surfacer 5550 accelerates the painting process, thanks to its modern, patented Axalta technology. The flash-off time is significantly shorter compared to standard wet-on-wet surfacers. This results in fast processing as well as providing outstanding top coat appearance.

- Simple 1:1 mixing ratio with Permasolid® Wet-on-Wet Speed Surfacer Hardener 3560 + 10% Permasolid® Speed Surfacer Accelerator 9065.
- Fast application in 1 to 2 coats.
- Excellent vertical stability.
- After incredible five-minute flash-off time, it can be scuff sanded or directly overcoated with Permahyd® Hi-TEC Base Coat 480 or Permahyd® Base Coat 280/285
- The modern Axalta technology ensures excellent gloss hold-out after top coating.
- Available in three colours: white, grey and black.
- Priomat® Reactive Pretreatment Wipes 4000 are required for very fast bare metal pre-treatment.
- Using the modern Speed-TEC product family within the Hi-TEC Performance System, delivers the shortest repair processes, significant energy cost savings and outstanding results.



Related Links

- > [Speed-TEC Product Family](#)
- > [Hi-TEC Performance System](#)
- > [Speed Repair System](#)
- > [Product Finder](#)